

Bush Hog® TOUGH SQUEALER® Series Rotary Cutters

BUSH HOG® TOUGH FEATURES

TOUGH EZ Clean Sloped Decks

TOUGH Sidebands With Welded Skids

TOUGH EZ Lube Drivelines

TOUGH Bush Hog® Gearboxes

TOUGH Quick Detach Gearbox Shields

TOUGH Full Length Replaceable Skids

TOUGH Powder Coat Paint



Model SQ160

MODELS	SQ142	SQ148	SQ160	SQ172	SQ184
Cutting Width	3 ft 6 inches	4 ft	5 ft	6 ft	7 ft
Cutting Capacity	1 inch dia.	1 inch dia.	2 inch dia.	2 inch dia.	2 inch dia.
Cutting Height	2 to 12 inches	2 to 12 inches	2 to 12 inches	2 to 12 inches	2 to 12 inches
Dimensions (width x length)	3 ft 7 inches x 6 ft 7 inches	4 ft 3 inches x 7 ft 1 inch	5 ft 5 inches x 8 ft 1 inch	6 ft 5 inches x 9 ft 2 inches	7 ft 5 inches x 10 ft 6 inches
Type Hitch	Cat I Standard and Quick Hitch	Cat I Standard and Quick Hitch	Cat I Standard and Quick Hitch	Cat I Standard and Quick Hitch	Cat I or II Standard and Quick Hitch
Deck Thickness	11 gauge	11 gauge	11 gauge	10 gauge	10 gauge
Sidebands	9 ³ / ₄ inches x 11 gauge	10 inches x 11 gauge	9 ³ / ₄ inches x 11 gauge	9 ³ / ₄ inches x 10 gauge	10 ¹ / ₄ inches x 10 gauge
Driveshaft	ASAE Cat 3	ASAE Cat 3	ASAE Cat 3	ASAE Cat 3	ASAE Cat 4
Gearbox	45 HP	45 HP	65 HP	65 HP	90 HP
Tractor PTO Speed	540 RPM	540 RPM	540 RPM	540 RPM	540 RPM
Driveline Protection	1/2 x 3 inches Grade 2 shearbolt	1/2 x 3 inches Grade 2 shearbolt	8 x 45 mm Metric Gr. 8.8 shearbolt Slip Clutch/Optional	10 x 55 mm Metric Gr. 8.8 shearbolt Slip Clutch/Optional	Slip Clutch Standard
Blade Holder(s)	Straight	Oval type	Oval type	Oval type	Oval type
Blades	3/8 x 3 inch uplift	3/8 x 3 inch uplift	1/2 x 4 inch uplift	1/2 x 4 inch uplift	1/2 x 4 inch uplift
Blade Tip Speed	11,400 FPM	13,029 FPM	14,335 FPM	14,963 FPM	14,963 FPM
Tires	Laminated or Solid Rubber	Laminated or Solid Rubber	Laminated or Solid Rubber	Laminated or Solid Rubber	Laminated
Tractor HP Range	10 - 25 PTO	15 - 30 PTO	25 - 40 PTO	30 - 45 PTO	50 - 70 PTO
Front and Rear Deflectors	Standard (Front Belting/Rear Band), All 5 Models				
Approximate Weight	397 lbs	455 lbs	636 lbs	764 lbs	1024 lbs
Warranty	1 year limited warranty with a 5 year gearbox limited warranty				
Options	Oval Blade Pan, Chain Shielding	Chain Shielding	Chain Shielding	Chain Shielding	Chain Shielding

FEATURES

Floating Frame Hitch • High blade tip speeds • Available in major tractor colors